



Compact all-in-one weather sensor for measurement of temperature, relative humidity, air pressure and radiation.

- **Parameters measured**
Temperature, relative humidity, air pressure, radiation
- **Measurement technology**
NTC/T, Capacitive/RH, MEMS capacitive/Pressure, Kipp&Zonen Pyranometer/Radiation
- **Product highlights**
Compact all-in-one weather sensor, low power, aspirated radiation shield, maintenance-free operation, open communication protocol
- **Interfaces**
RS485 with supported protocols UMB-Binary, UMB-ASCII, Modbus-RTU, Modbus-ASCII, XDR and SDI-12
- **Article number**
8374.U01

From the WS product family of professional intelligent measurement transducers with digital interface for environmental applications. Integrated design with ventilated radiation protection for measuring: Air temperature, relative humidity, air pressure and radiation. One external temperature or rain sensor is connectable.

General

| | |
|--------|----------------|
| Weight | Approx. 1.3 kg |
|--------|----------------|

| | |
|----------------------------|---|
| Interface | RS485, 2 - wire, half - duplex |
| Power supply | 4...32 VDC |
| Power supply | 5...11 VDC (electronics with limited precision of measurements) |
| Power supply | 24 VDC +/- 10% |
| Power consumption | 40 VA |
| Operating temperature | -50...60 °C |
| Operating rel. humidity | 0...100 % RH |
| Dimensions | Ø approx. 150 mm, height approx. 268 mm |
| Protection level housing | IP66 |
| Mast mounting suitable for | Mast diameter 60 - 76 mm |

| Temperature | |
|-----------------|--|
| Principle | NTC |
| Measuring range | -50 ... 60 °C |
| Unit | °C |
| Accuracy | ±0.2 °C (-20...50 °C), otherwise ±0.5 °C (>-30 °C) |

| Relative humidity | |
|-------------------|----------------|
| Principle | Capacitive |
| Measuring range | 0 ... 100 % RH |
| Unit | % RH |
| Accuracy | ±2 % RH |

| Air pressure | |
|-----------------|----------------------|
| Principle | MEMS capacitive |
| Measuring range | 300 ... 1200 hPa |
| Unit | hPa |
| Accuracy | ±0.5 hPa (0...40 °C) |

| Radiation | |
|--|-----------------------|
| Unit | W/m ² |
| Response time (95%) | < 18 s |
| Non-stability(change/year) | < 1 % |
| Non-linearity (0 to 1000 W/m ²) | < 1 % |
| Directional error (at 80° with 1000 W/m ²) | < 20 W/m ² |
| Temperature dependence of sensitivity | < 5 % (-10 to +40 °C) |
| Tilt error (at 1000 W/m ²) | < 1 % |
| Spectral range | 300...2800 nm |
| Measuring range | 2000 W/m ² |
| Altitude | 0...60 ° Azimuth |