

## SF<sub>6</sub> gas detectors

### For quick tracing of small SF<sub>6</sub> leaks

3-033-R002

#### SF<sub>6</sub>-LeakPointer

The cordless battery operated device measures in seven levels of sensitivity within a short response time. Even after the detection of large leaks the device returns to zero position quickly.

The SF<sub>6</sub> LeakPointer is easy to operate with one hand. Leakages can be easily detected via the clearly visible LED display or the audible signal (can be switched off). Continuous operation of the device is possible.



- Quick response time
- Quick "Reset" time
- Detection of leaks of up to 5 g / year
- Comfortable single-handed operation
- Battery-operated (with capacity check)
- Temperature-compensated

3-033-R002

**SF<sub>6</sub>-LeakPointer**

**Technical data:**

Dimensions with case: W 65 mm, H 229 mm, D 65 mm
Weight with case and accessories: 560 g
Power supply: 2 x 1.5 V alkaline batteries C LR14 (Not included in the delivery)
Measuring principle: high voltage ionisation
Sensitivity: 5 g SF <sub>6</sub> / year
Operating temperature: 0 °C to +52 °C
Ambient moisture: max. 90 % relative moisture, non condensing during operation
Response time T90: approx. 1 second
Reset time: approx. 1 second
Indication: 7 LED measuring range indication and acoustic signal (disconnectable)
Sensor length: 355 mm

**Standard equipment:**

Carrying case
Spare sensor
1 operating manual (multilingual) on CD-ROM

**Optional accessories at an extra charge:**

Spare sensor kit (3 pieces)	5002016
Spare case	5010354
Additional operating manual on CD-ROM	6-0004-R213

**Packing:**

Packing for 3-033-R002	6-0004-R039
------------------------	-------------

