

Product Information

VD-008..080GR

Flow Switch VD-...GR




- **Highly reproducible**
- **Precise, stepless adjustment of the switching value**
- **Insensitive to dirt**
- **Short installation length**

Characteristics

The volume flow raises a piston (fitted with a magnet) out from a valve seat against a spring force. The piston actuates a hermetically separated reed switch.

Technical data

Switch	reed switch	
Nominal width	DN 8..80	
Process connection	female thread G 1/4..G 3	
Switching range	1..600 l/min	for details see table "Ranges"
Qmax.	to 720 l/min	
Tolerance	±5 % of full scale value	
Pressure resistance	G 1/4..G 1 - PN 25 bar G 1 1/4 ..G 3 - PN 16 bar	
Medium temperature	-20..+120 °C	
Ambient temperature	-20..+70 °C	
Media	water (oils and gases available on request)	
Wiring	changeover no. 0.213	
		
Switching voltage	max. 175 V DC / 120 V AC	
Switching current	max. 0.25 A DC / 0.18 A AC	
Switching capacity	max. 5 W / VA	
Protection class	2 - safety insulation	
Ingress protection	IP 44, optionally IP 65	
Connection	plug DIN 43650-A / ISO 4400	
Materials medium-contact	Rg 5 / Rg 6 nickelled, POM, 1.4310, CW614N, NBR, hard ferrite	
Non-medium-contact materials	ABS, PA	

Weight	see table "Dimensions and weights"
Installation location	Standard: horizontal inwards flow; switching head not recommended underneath; other installation positions are possible; the installation position affects the switching point and range.

Ranges

Details in the table correspond to horizontal inwards flow with decreasing flow rate.

G	Nominal width	Switching range l/min H ₂ O	Q _{max.} recommended	Type
G 1/4 G	DN 8	1 - 10 4 - 20	15	VD-008GR010
3/8	DN 10		25	VD-008GR020
			20	VD-010GR010
			30	VD-010GR020
G 1/2	DN 15		20	VD-015GR010
			30	VD-015GR020
G 3/4	DN 20	20	VD-020GR010	
		40	VD-020GR020	
		60	VD-020GR040	
		80	VD-020GR060	
		20	VD-025GR010	
		40	VD-025GR020	
G 1	DN 25	60	VD-025GR040	
		85	VD-025GR060	
		90	VD-032GR040	
		100	VD-032GR060	
G 1 1/4	DN 32	145	VD-032GR100	
		30 - 100 50 - 150	200	VD-032GR150
		100	VD-040GR060	
G 1 1/2	DN 40	20 - 60 30 - 100	150	VD-040GR100
		220	VD-040GR150	
		50 - 150	250	VD-050GR150
G 2	DN 50	290	VD-050GR200	
		600	VD-080GR330	
G 3	DN 80	720	VD-080GR600	


Special ranges are available

Product Information

VD-008..080GR

Dimensions and weights

G	Types	H	L	SW	X	Weight kg
G 1/4 G	VD-008GR	150	65	29	12	1.0
3/4 G 1/4 G	VD-010GR					
3/4	VD-015GR					
G 1	VD-020GR					
G 1 1/4	VD-025GR	156	80	32	16	1.1
G 1 1/2	VD-032GR			41	18	1.3
G 2	VD-032GR			52	13	2.1
G 3	VD-040GR			113	59	2.8
	VD-050GR			137	72	4.0
	VD-080GR			148	100	7.0



Handling and operation

Note

- Include straight calming section of 5 x DN in inlet and outlet
- Include a filter if the media are dirty (use magnetic filter for ferritic components).
- It must be ensured that the values given for voltage, current, and power are not exceeded.
- When switched on, a load must be connected in series.
- The electrical details apply to ohmic loads. Capacitive, inductive and lamp loads must be operated using a protective circuit.

Adjustment

To adjust the switching point, the fixing screw for the switching head must be loosened. The switching head can then be rotated. Turning to the right increases the switching point, and vice-versa. Then retighten the fixing screw.



Ordering code

VD - 1. 2. 3. 4. 5.
VD -

1. Nominal width	
008	DN 8 - G 1/4
010	DN 10 - G 3/8
015	DN 15 - G 1/2
020	DN 20 - G 3/4
025	DN 25 - G 1
032	DN 32 - G 1 1/4
040	DN 40 - G 1 1/2
050	DN 50 - G 2
080	DN 80 - G 3
2. Process connection	
G	female thread
3. Connection material	
R	red bronze
4. Switching range H ₂ O for horizontal inwards flow	
010	1 - 10 l/min 4
020	- 20 l/min 10 -
040	40 l/min 20 -
060	60 l/min 30 -
100	100 l/min 50 -
150	150 l/min 100 -
200	200 l/min 180 -
330	330 l/min 300 -
600	600 l/min
5. Optionally for ATEX	
A	for switching head ATEX A-V1 (The switching head is ordered in addition)

Options

- Special plugs, Tuchel / Harting
- Signal lamp red or red/green in the plug DIN 43650-A
- Other signal lamp
- Protection class IP 65
- Temperature display 0..120 °C
- Temperature monitoring 40..90 °C
- Temperature resistant up to 150 °C
- Metal cap
- Switch contact SPDT change over 250 V AC 0,35 A 30 VA - increased hysteresis depending on switching value. Only available with fixed switch point.
- Switching ranges for oil or gas
- Special values
- Internal parts brass or stainless steel

Ordering information

- Specify direction of flow, medium, and switching range.
- For oils. State viscosity, temperature and designation (e.g. ISO VG 68) (enquire about switching range).
- For gases, state pressure (relative or absolute), temperature and medium (e.g. air) (request switching range).

INSTRUFIBER

Fibra Óptica Cabo Rede Instrumentação Energia Ferramenta

