



Product Description

ComputerPOSCable, 22 AWG solid tinned copper conductors, solid FEP insulation, twisted pairs, overall Beldfoil® (100% coverage) + tinned copper braid shield (90% coverage), 22 AWG solid tinned copper drain wire, FEP jacket, plenum rated

Technical Specifications

Product Overview

Suitable Applications:	point of sale; rs-485 applications; extreme high/low temperature environments; computer communication; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; panel wiring
------------------------	--

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	2	22	Solid	TC - Tinned Copper

Insulation

Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
FEP - Fluorinated Ethylene Propylene	0.016 in (0.41 mm)	0.058 in (1.5 mm)	Red & Blue, Black & Yellow

Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	22 AWG (Solid) TC
Braid	Tinned Copper (TC)	90%	

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
FEP - Fluorinated Ethylene Propylene	0.017 in (0.43 mm)	0.24 in (6.1 mm)

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Nom. Delay	Nom. Inductance	Nom. Velocity of Prop.	Max. Current
20.6 Ohm/1000ft	15.5 pF/ft (50.9 pF/m)	27 pF/ft (89 pF/m)	100 Ohm	1.46 ns/ft	0.17 µH/ft (0.56 µH/m)	70%	2.3 Amps per Conductor at 25°C
Nom Outer Shield DCR@Cond DCR1-cnvr:		2.1 Ohm/1000ft (6.9 Ohm/km)					

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss (Attenuation)
0.3	0.4 dB/100m
0.6	0.53 dB/100m
1	0.65 dB/100m
1.5	0.78 dB/100m

Voltage

UL Voltage Rating
300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
200°C	-70°C to +150°C

Bend Radius

Stationary Min.	Installation Min.
2.4 in (61 mm)	2.4 in (61 mm)

Max. Pull Tension:	80.7 lbs (36.6 kg)
Bulk Cable Weight:	44 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Outdoor, Sunlight Resistance, Oil Resistance
Flammability / Reaction to Fire:	NFPA 262 (UL910), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	1268A

History

Update and Revision:	Revision Number: 0.463 Revision Date: 09-07-2025
----------------------	--

Part Numbers

Variants

Item #	Color	UPC	Footnote
1269A 0101000	Black	612825110064	C

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2025 instrufiber, Inc

All Rights Reserved.

Although instrufiber makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

instrufiber provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will instrufiber be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if instrufiber has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of instrufiber products are subject to instrufiber's standard terms and conditions of sale.

instrufiber believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of instrufiber's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.